

MAINTENANCE

- 1.** After installing the floor, we recommend a first cleaning to remove and loosen dirt or debris that may have been introduced during the installation process. Sweep and vacuum the floor surface to ensure removal of all loose dust, dirt, and debris. Use a damp mop with clean, warm, water and a neutral floor cleaner to scrub the flooring surface. Use warm, clean water, rinse several times as needed, then use a dry mop or wet vacuum to remove the water and allow to dry. Thereafter, clean regularly with a damp mop with a vinyl floor cleaner. Do not use excessive water.
- 2.** Do not wax your Click N Go flooring.
- 3.** Please check any new cleaning agents on a small test patch of the floor in an inconspicuous area, and avoid using harsh cleaners or ammonia based cleaning products.
- 4.** If your floor has been exposed to excessive amounts of water due to flooding remove the water as quickly as possible. A dehumidifier should be promptly turned on in the room to reduce the moisture levels back to normal. Do not dry the room below the normal moisture level .
- 5.** To protect the flooring surface from abrasive dirt and debris use walk off mats near entryways.
- 6.** Do not allow pets with unclipped nails to damage your vinyl flooring. It may result in severe scratching to the surface. The same is true for any high-heeled shoes that do not have proper tips on the heels can damage your floor.
- 7.** Avoid exposure to direct sunlight for prolonged periods of time. During peak sunlight hours, use drapes or blinds to minimize the direct sunlight on the vinyl flooring. Most types of flooring will be affected by continuous strong sunlight. In addition, excessive temperatures are not good for resilient floors. Some natural ventilation or intermittent air conditioning in vacant homes should be considered. Long term continuous inside temperatures over 95 F° combined with strong direct sunlight will damage the flooring and cause the installation to fail.