

Flooring by SelechTech, Inc.

Construction	
Dimensions (finished surface)	18.5" x 18.5" 47.0 cm x 47.0 cm
Coverage	2.38 sq ft/tile 0.22 sq meter/tile
Thickness	5/16" 7.94 mm
Commercial Wear Surface	10 mil (0.25mm) PVC Ceramic/Urethane Wear Coat
Weight	5.4 lbs/tile
Packaging	8 tiles/box 19.04 SF/ box


















Environmental Quality

Air Quality Meets Requirement for LEED IEQ 4.3	CA Prop. 1350 IEQ Protocol
Recycled Plastic Content	70%
Quality System	ISO 9001
LEED	Use of Place N' Go flooring can contribute to points in Materials and Resources, Regional Materials, Indoor Environmental Quality, and Innovation Credit categories.



Easy Place N' Go Installation

Place N' Go flooring is a unique interlocking flooring that requires no adhesive. Its water-resistance and durability make it the perfect choice for problem areas like basements and its attractive surface makes it perfect for many other areas in your home.

When installing **Place N' Go** you don't use any underlayment or moisture barriers.

Place N' Go is the easiest flooring product to install: just measure, cut, then tap the tiles together.

Recycled and Reliable

Place N' Go flooring is made with a resilient recycled plastic that resists moisture and installs easily over a variety of problem subfloors, including old basement floors.

Our Commitment

Our company is committed to changing the flooring industry to help better our environment. **Place N' Go** has one of the highest recycled contents (70%) of any decorative flooring product, and it is 100% recyclable into new **Place N' Go** products.

Better still, **Place N' Go**'s interlocking systems eliminates the need for adhesives and the VOC's that come with them.



Lay Down Place N' Go



Lock the Seam Using a Simple Mallet



No adhesives... No special tools... No special skills...



Contact Us For More Information:

SelecTech, Inc. 33 Wales Ave, Unit F, Avon, MA 02322 Phone (877.738.4537) Email: contactus@selectechinc.com Visit our website at www.placengo.com